

# BOLTING AND RING GASKET DATA FOR API AND ANSI FLANGES

**MT. HOOD FASTENER CO.**

888.323.3434    WWW.MTHOODFASTENER.COM

## API FLANGES

API Pressure Rating	Flange Size & Bore	Ring Gasket API No.	No. of Studs	Size	Stud with Two Nuts
					Length
2000 lb WOG 4000 lb Test	2-1/16"	R or RX 23	8	5/8"	4-3/4"
	2-9/16"	R or RX 26	8	3/4"	5-1/4"
	3-1/8"	R or RX 31	8	3/4"	5-1/2"
	4-1/16"	R or RX 37	8	7/8"	6-1/4"
	7-1/16"	R or RX 45	12	1"	7-1/4"
	9"	R or RX 49	12	1-1/8"	8-1/4"
	11"	R or RX 53	16	1-1/4"	9"
	13-5/8"	R or RX 57	20	1-1/4"	9-1/4"
	16-3/4"	R or RX 65	20	1-1/2"	10-1/2"
	21-1/4"	R or RX 73	24	1-5/8"	12"
3000 lb WOG 6000 lb Test	2-1/6"	R or RX 24	8	7/8"	6-1/4"
	2-9/16"	R or RX 27	8	1"	6-3/4"
	3-1/8"	R or RX 31	8	1-1/8"	6-1/4"
	4-1/16"	R or RX 37	8	1-1/8"	7-1/4"
	7-1/16"	R or RX 45	12	1-1/8"	8-1/4"
	9"	R or RX 49	12	1-3/8"	9-1/4"
	11"	R or RX 53	16	1-3/8"	9-3/4"
	13-5/8"	R or RX 57	20	1-3/8"	10-1/2"
	16-3/4"	R or RX 66	20	1-5/8"	12"
	20-3/4"	R or RX 74	20	2"	14-3/4"
5000 lb WOG 10,000 lb Test	2-1/16"	R or RX 24	8	7/8"	6-1/4"
	2-9/16"	R or RX 27	8	1"	6-3/4"
	3-1/8"	R or RX 35	8	1-1/8"	7-1/2"
	4-1/16"	R or RX 39	8	1-1/4"	8-1/4"
	7-1/16"	R or RX 46	12	1-3/8"	11"
	9"	R or RX 50	12	1-5/8"	12-1/4"
	11"	R or RX 54	12	1-7/8"	14"



API Pressure Rating	Flange Size & Bore	Ring Gasket API No.	No. of Studs	Size	Stud with Two Nuts			
					Length			
2000 lb WOG 4000 lb Test 6 BX	26-3/4"	BX 167	20	1-3/4"	14			
3000 lb WOG 6000 lb Test 6 BX	26-3/4"	BX 168	24	2"	17-1/4"			
5000 lb WOG 10,000 lb Test 6 BX	26-3/4"	BX 160	16	1-5/8"	12-3/4"			
					BX 162	16	1-7/8"	14-3/4"
					BX 163	20	2"	17-3/4"
					BX 165	24	2"	19"
10,000 lb WOG 15,000 lb Test 6 BX	26-3/4"	BX 150	8	3/4"	5-1/4"			
					BX 151	8	3/4"	5-1/4"
					BX 152	8	3/4"	5-1/2"
					BX 153	8	7/8"	6-1/4"
					BX 154	8	1"	7"
					BX 155	8	1-1/8"	8-1/4"
					BX 169	12	1-1/8"	9"
					BX 156	12	1-1/2"	11-1/2"
					BX 157	16	1-1/2"	13-1/4"
					BX 158	16	1-3/4"	15-1/4"
					BX 159	20	1-7/8"	17-1/2"
					BX 162	24	1-7/8"	17-3/4"
					BX 164	24	2-1/4"	22-3/4"
					BX 166	24	2-1/2"	24"
15,000 lb WOG 22,000 lb Test 6 BX	26-3/4"	BX 150	8	3/4"	5-1/2"			
					BX 151	8	7/8"	5-3/4"
					BX 152	8	7/8"	6-1/4"
					BX 153	8	1"	7"
					BX 154	8	1-1/8"	7-3/4"
					BX 155	8	1-3/8"	9-1/2"
					BX 156	16	1-1/2"	13"
					BX 157	16	1-7/8"	16"
20,000 lb WOG 6 BX	26-3/4"	BX 151	8	1"	7-3/4"			
					BX 152	8	1-1/8"	8-1/2"
					BX 153	8	1-1/4"	9-1/2"
					BX 154	8	1-3/8"	10-1/4"
					BX 155	8	1-3/4"	12-1/2"
					BX 156	16	2"	17-3/4"

Note: Studs are measured on end to end basis.

## TORQUE REQUIRED TO PRODUCE BOLT STRESS

Torque Data For Use With Alloy Steel Stud Bolts  
Load in pounds on stud bolt when torque loads are applied.

Charts replicated from Dan-Loc brochures and charts.

NOMINAL DIAMETER OF BOLT (Inches)	NUMBER OF THREADS (Per Inch)	DIAMETER AT ROOT OF THREAD (Inches)	AREA AT ROOT OF THREAD (Sq. Inch)	STRESS					
				30,000 PSI		45,000 PSI		60,000 PSI	
				Torque Ft/Lbs	Compression Lbs	Torque Ft/Lbs	Compression Lbs	Torque Ft/Lbs	Compression Lbs
1/4	20	.185	.027	4	810	6	1215	8	1620
5/16	18	.240	.045	8	1350	12	2025	16	2700
3/8	16	.294	.068	12	2040	18	3060	24	4080
7/16	14	.345	.093	20	2790	30	4185	40	5580
1/2	13	.400	.126	30	3780	45	5670	60	7560
9/16	12	.454	.162	45	4860	68	7290	90	9720
5/8	11	.507	.202	60	6060	90	9090	120	12120
3/4	10	.620	.302	100	9060	150	13590	200	18120
7/8	9	.731	.419	160	12570	240	18855	320	25140
1	8	.838	.551	245	16530	368	24795	490	33060
1-1/8	8	.963	.728	355	21840	533	32760	710	43680
1-1/4	8	1.088	.929	500	27870	750	41805	1000	55740
1-3/8	8	1.213	1.155	680	34650	1020	51975	1360	69300
1-1/2	8	1.338	1.405	800	42150	1200	63225	1600	84300
1-5/8	8	1.463	1.680	1100	50400	1650	75600	2200	100800
1-3/4	8	1.588	1.980	1500	59400	2250	89100	3000	118800
1-7/8	8	1.713	2.304	2000	69120	3000	103680	4000	138240
2	8	1.838	2.652	2200	79560	3300	119340	4400	159120
2-1/4	8	2.088	3.423	3180	102690	4770	154035	6360	205380
2-1/2	8	2.338	4.292	4400	128760	6600	193140	8800	257520
2-3/4	8	2.588	5.259	5920	157770	8880	236655	11840	315540
3	8	2.838	6.324	7720	189720	11580	284580	15440	379440

The table above reflects the results of many tests to determine the relation between torque and bolt stress. Values are based on steel bolting well lubricated with a heavy graphite and oil mixture.